


# PRESTON

CCT selectable halo effect IP65 circular polycarbonate fitting for commercial indoor areas



CCT SELECTABLE  
3000K/4000K



AVAILABLE WITH MICROWAVE  
SENSOR FITTED



### APPLICATIONS

- For commercial interior use in corridors, stairwells, toilets and changing rooms

### CONSTRUCTION

- Polycarbonate base and front trim
- Base allows side conduit entry
- Opal polycarbonate diffuser
- Hinged gear tray for easy access to terminal block and fixing points
- Piano key terminal block for easy installation and allows loop-in/loop-out wiring

### TECHNICAL DETAILS

- 160 lm/W
- Available in 2 sizes:
  - 21W nom., 18.9W act., 2,083 lm, 110 l.lm/cW
  - 32W nom., 28.3W act., 2,900 lm, 102 l.lm/cW
- CRI>80
- CCT Selectable between 3000K/4000K
- Branded ENEC approved, flicker free, LED driver
- Emergency maintained 3 hr versions available, as listed (suffix M3L)

### OPTIONS

**DIMMING** DD (DALI or Switch Dim) or CF (Corridor Function) available. Add suffix DD or CF as required

**SPECIALIST EMERGENCY** Self-test emergency (Suffix STM3) or DALI addressable emergency (Suffix DAM3) options available

**SENSOR** Available with built in microwave sensor. Suffix MW

**DIMMING & SENSOR** A popular combination is corridor function & microwave sensor. Suffix CFMW

**SMART WIRELESS** lighting control and addressable test options are available. See pages 100-103 or contact our technical team for details

ORDER CODE	DESCRIPTION
NPE21/830-840	Preston 21W LED IP65 White Bezel 830-840
NPE21/M3L/830-840	Preston 21W LED IP65 White Bezel M3 Lithium 830-840
NPE32/830-840	Preston 32W LED IP65 White Bezel 830-840
NPE32/M3L/830-840	Preston 32W LED IP65 White Bezel M3 Lithium 830-840

