

TEXAS

Batten available in 4', 5' and 6' sizes in standard and high-output



APPLICATIONS

- Suitable for commercial or domestic applications

CONSTRUCTION

- Conventional batten width steel body
- White RAL9016 powder coated finish
- Opal polycarbonate LED diffuser
- BESA fixing points on rear
- LEDs on metal core PCB
- Central cable entry point
- Piano key terminal block for speed of installation and loop-in / loop-out wiring
- Provided with security screws to stop removal of front cover from the body

TECHNICAL DETAILS

- 160 lm/W
- Available in 3 sizes:
 - 1x4', 24W, 2,970 lm, 126 l.lm/c.W
 - 2x4', 46W, 5,700 lm, 125 l.lm/c.W
 - 1x5', 40W, 4,760 lm, 120 l.lm/c.W
 - 2x5', 64W, 7,620 lm, 119 l.lm/c.W
 - 1x6', 49W, 6,040 lm, 124 l.lm/c.W
 - 2x6', 77W, 8,715 lm, 113 l.lm/c.W
- CRI>80
- CCT 4000K
- Branded ENEC approved flicker free driver
- Emergency maintained 3 hr versions available as listed (suffix M3L)

OPTIONS

TEXAS can be fitted with either of the batten-mount sensors listed on page 98, which are to be purchased separately

ORDER CODE	DESCRIPTION
NTE1X4/840	Texas LED Single 4Ft Batten 840
NTE1X4/M3L/840	Texas LED Single 4Ft Batten M3 Lithium 840
NTE2X4/840	Texas LED Twin 4Ft Batten 840
NTE2X4/M3L/840	Texas LED Twin 4Ft Batten M3 Lithium 840
NTE1X5/840	Texas LED Single 5Ft Batten 840
NTE1X5/M3L/840	Texas LED Single 5Ft Batten M3 Lithium 840
NTE2X5/840	Texas LED Twin 5Ft Batten 840
NTE2X5/M3L/840	Texas LED Twin 5Ft Batten M3 Lithium 840
NTE1X6/840	Texas LED Single 6Ft Batten 840
NTE1X6/M3L/840	Texas LED Single 6Ft Batten M3 Lithium 840
NTE2X6/840	Texas LED Twin 6Ft Batten 840
NTE2X6/M3L/840	Texas LED Twin 6Ft Batten M3 Lithium 840

