

COUGAR

IP65 aluminium die-cast asymmetric floodlight



APPLICATIONS

- For use on building facades, area floodlighting round buildings and industrial premises, perimeter and security lighting

CONSTRUCTION

- Aluminum die-cast body painted black, RAL9017, with fine textured finish
- 4mm clear toughened glass front panel held in place with stainless steel screws
- IP65 rated breather valve fitted to help maintain IP65 rating in all weathers
- IP65 stainless steel cable gland fitted for incoming power cable
- Pre-wired with 0.7m of 3-core x 1.0mm² H05RN-F flex
- LED module screw fixed to body. Polycarbonate lens on each LED for a precise asymmetric light distribution
- Supplied with a black painted steel mounting bracket

OPTIONS

- Wattage: Choice of 50W, 100W, 150W and 200W

ORDER CODE	AVAILABILITY			POWER (W)	CCT (K)	LUMENS (lm)	EFFICACY (lm/W)	CRI (Ra)	DRIVERS PER MCB	COLOUR
	DK	FI	SE							
NCU50/740		-	-	52	4000	6,425	124	>70	B10=3 B16=6 C10=6 C16=10	BLACK
NCU100/740		-	-	99	4000	10,850	110	>70	B16=3 C16=6	BLACK
NCU150/740		-	-	151	4000	16,420	108	>70	B16=3 C16=6	BLACK
NCU200/740		-	-	200	4000	23,050	115	>70	B16=3 C16=6	BLACK