

NVC UK - NVC Lighting Limited
NVC Park 201, Hollymoor Way, Rubery,
Birmingham, B31 5HE
T +44 (0)121 457 6340
E sales@nvcuk.com

NVC NORDICS - NVC Lighting AB
Albybergsringen 3b 137 69 Österhaninge
T +46(0)8 735 55 40
Sweden info@nvc-lighting.se
Finland info@nvc-lighting.fi
Denmark info@nvc-lighting.dk



DATASHEET

ACCESSORIES

LiFe Self Test M3 Emergency Pack For Recessed Product Ranges

Plug And Play Option For A Range Of Fittings
Comes Complete With Loop in / Loop Out Connections
Lithium Iron Phosphate Battery LiFePO4



GENERAL INFORMATION	
Product Code	N/REC/STM3/PACK/V2
Product Range	LED Panels
Product Category	LED Panels
IP Rating	N/A
IK Rating	N/A
Warranty	N/A
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=N/A
Dimensions Square/Rectangular (L x W x H) (mm)	L=330, W=61, H=30
Cut-out Size (mm)	N/A
Product Weight (Kg)	0.41
CONSTRUCTION	
Body Material	PC
Body Colour	White
Optical Material	N/A
Optical Finish	N/A
Termination	4x2x2.5mm sq. Push In Terminal
Driver - Intergal or Remote	Remote
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	N/A
Power Consumption (W)	N/A
LED Lumens (lm/W)	N/A
Efficacy (l.m/c.W)	N/A
Operating Temp. (Min/Max)	0°C to 40°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	N/A
Colour Rendering Index (CRI)	N/A
Lumen Depreciation	N/A
SDCM	N/A
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50/60Hz
In Rush	N/A
Drivers per MCB*	N/A
Class	Class 2
Power Factor	N/A
Cable Entry	Prewired
ELECTRICAL OUTPUT	
Forward Current (mA)	35 to 100
Forward Voltage (Vf)	20 to 55
EMERGENCY DATA	
Mode of Operation	Non-Maintained
Battery Duration	3 hours
Battery Type	LiFePO4
Battery Specification	6.4V 1.5Ah
Emergency Lumens	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5055943077027

* GUIDE ONLY

