

DATASHEET

CLEVELAND

Cleveland LED Twin 4Ft IP65 Non Corrosive 840

Energy Efficiency Classification Class D
 Strong PC Enclosure & Stainless Steel Clips
 ENEC Approved Flicker Free Driver



GENERAL INFORMATION	
Product Code	NCV2X4/840
Product Range	Industrial
Product Category	Industrial
IP Rating	65
IK Rating	IK10
Warranty	5 Years Unlimited
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=N/A
Dimensions Square/Rectangular (L x W x H) (mm)	L=1250, W=110, H=70
Cut-out Size (mm)	N/A
Product Weight (Kg)	2.08
CONSTRUCTION	
Body Material	PC
Body Colour	Grey
Optical Material	N/A
Optical Finish	N/A
Termination	3x2x2.5mm sq. Push In Terminal
Driver - Integal or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	D
Luminaire Lumens (lm)	4845
Power Consumption (W)	40
LED Lumens (lm/W)	150
Efficacy (l.lm/c.W)	126
Operating Temp. (Min/Max)	-20°C to 25°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	4000
Colour Rendering Index (CRI)	>80
Lumen Depreciation	L70 50000
SDCM	<5
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50/60Hz
In Rush	<25A
Drivers per MCB*	B10=20 B16=30 C10=30 C16=40
Class	Class 1
Power Factor	>0.95
Cable Entry	Side / Base
ELECTRICAL OUTPUT	
Forward Current (mA)	2 x 300
Forward Voltage (Vf)	56
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Emergency Lumens	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5055943066472
S NUMBER	4344022

* GUIDE ONLY

