

## DATASHEET

### KANSAS LIFE

Kansas LiFe Twinspot IP65 LED Non-Maint. DALI

Lithium Iron Phosphate (LiFePO4) Battery  
 Heads Can Be Rotated And Tilted  
 Loop In / Loop Out Mains Terminal Block



GENERAL INFORMATION	
Product Code	NKS/IP65/DA/NM3
Product Range	Emergency
Product Category	Emergency
IP Rating	65
IK Rating	N/A
Warranty	7 Years Unlimited
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=N/A
Dimensions Square/Rectangular (L x W x H) (mm)	L=297, W=70, H=282
Cut-out Size (mm)	N/A
Product Weight (Kg)	1
CONSTRUCTION	
Body Material	ABS/PC
Body Colour	White
Optical Material	N/A
Optical Finish	N/A
Termination	3x2x2.5mm sq. Push In Terminal
Driver - Integal or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	768
Power Consumption (W)	7
LED Lumens (lm/W)	N/A
Efficacy (l.lm/c.W)	N/A
Operating Temp. (Min/Max)	0°C to 40°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	7500
Colour Rendering Index (CRI)	N/A
Lumen Depreciation	N/A
SDCM	N/A
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50/60Hz
In Rush	N/A
Drivers per MCB*	N/A
Class	Class 1
Power Factor	N/A
Cable Entry	Side
ELECTRICAL OUTPUT	
Forward Current (mA)	N/A
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	Non-Maintained Self Test
Battery Duration	3 hours
Battery Type	LiFePO4
Battery Specification	3.2V 5.5Ah
Emergency Lumens	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5056673203953

\* GUIDE ONLY

