

## DATASHEET

### NEBRASKA LIFE

Nebraska LiFe LED IP65 Maint. Bulkhead ISO Legend Pack

Energy Efficiency Classification Class D  
 Geartray Fixed to Diffuser For Easy Access  
 ISO 7010 Legend Pack



GENERAL INFORMATION	
Product Code	NNE/M3/ISO
Product Range	Emergency
Product Category	Emergency
IP Rating	65
IK Rating	N/A
Warranty	7 Years Unlimited
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=0, H=0
Dimensions Square/Rectangular (L x W x H) (mm)	L=352, W=110, H=65
Cut-out Size (mm)	0
Product Weight (Kg)	0.8
CONSTRUCTION	
Body Material	PC
Body Colour	White
Optical Material	N/A
Optical Finish	N/A
Termination	4x2x2.5mm sq. Push In Terminal
Driver - Integal or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	Mains-195 Emergency-133
Power Consumption (W)	2.1
LED Lumens (lm/W)	N/A
Efficacy (l.lm/c.W)	N/A
Operating Temp. (Min/Max)	0°C 40°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	N/A
Colour Rendering Index (CRI)	N/A
Lumen Depreciation	L80 100000
SDCM	N/A
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50/60Hz
In Rush	N/A
Drivers per MCB*	B10:15 B16:24 C10:25 C16:40
Class	Class 2
Power Factor	N/A
Cable Entry	Multiple
ELECTRICAL OUTPUT	
Forward Current (mA)	N/A
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	Maintained
Battery Duration	3 Hours
Battery Type	LiFePO4
Battery Specification	3.2V 1.1Ah
Emergency Lumens	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5056673207746

\* GUIDE ONLY

