

## DATASHEET

### NEBRASKA LIFE

Nebraska LiFe Recessed Mounting Kit

Recessed Mounting Kit  
 Recessed Bulkhead Body Into Ceiling  
 Easy Installation



| GENERAL INFORMATION                            |                   |
|--|-------------------|
| Product Code                                   | NNE/RMK           |
| Product Range                                  | Emergency         |
| Product Category                               | Emergency         |
| IP Rating                                      | N/A               |
| IK Rating                                      | N/A               |
| Warranty                                       | N/A               |
| DIMENSION/WEIGHT                               |                   |
| Dimensions Circular (DIA x H) (mm)             | DIA=0, H=37       |
| Dimensions Square/Rectangular (L x W x H) (mm) | L=392, W=150, H=0 |
| Cut-out Size (mm)                              | 360x120           |
| Product Weight (Kg)                            | 0.46              |
| CONSTRUCTION                                   |                   |
| Body Material                                  | PC                |
| Body Colour                                    | White             |
| Optical Material                               | N/A               |
| Optical Finish                                 | N/A               |
| Termination                                    | N/A               |
| Driver - Integal or Remote                     | N/A               |
| PACKAGING                                      |                   |
| Carton Dimensions (mm)                         | N/A               |
| Quantity per Outer Carton                      | N/A               |
| Total Weight inc. Carton (Kg)                  | N/A               |

| LUMINAIRE PERFORMANCE        |               |
|------------------------------|---------------|
| Energy Rating                | N/A           |
| Luminaire Lumens (lm)        | N/A           |
| Power Consumption (W)        | N/A           |
| LED Lumens (lm/W)            | N/A           |
| Efficacy (l.lm/c.W)          | N/A           |
| Operating Temp. (Min/Max)    | N/A N/A       |
| LIGHT SOURCE                 |               |
| Type                         | N/A           |
| Correlated Colour Temp.      | N/A           |
| Colour Rendering Index (CRI) | N/A           |
| Lumen Depreciation           | N/A           |
| SDCM                         | N/A           |
| ELECTRICAL INPUT             |               |
| VOLTAGE (V)                  | N/A           |
| Operating Frequency          | N/A           |
| In Rush                      | N/A           |
| Drivers per MCB*             | N/A           |
| Class                        | N/A           |
| Power Factor                 | N/A           |
| Cable Entry                  | N/A           |
| ELECTRICAL OUTPUT            |               |
| Forward Current (mA)         | N/A           |
| Forward Voltage (Vf)         | N/A           |
| EMERGENCY DATA               |               |
| Mode of Operation            | N/A           |
| Battery Duration             | N/A           |
| Battery Type                 | N/A           |
| Battery Specification        | N/A           |
| Emergency Lumens             | N/A           |
| DIMMING                      |               |
| DALI                         | N/A           |
| OTHER                        | N/A           |
| Switch Dim                   | N/A           |
| Corridor Function            | N/A           |
| SENSORS                      |               |
| Microwave                    | N/A           |
| PIR                          | N/A           |
| STANDARDS/APPROVALS          |               |
| CE Marked                    | Yes           |
| Certificate of Conformity    | Yes           |
| Accreditations               | N/A           |
| BARCODE                      |               |
| EAN NUMBER                   | 5056673207807 |

\* GUIDE ONLY

