

DATASHEET

PASCO

Pasco 9-14-18W LED Bulkhead IP65 White Opal MW 830-40-65

IP65 Decorative LED Bulkhead
 PC Construction And PC Opal Diffuser
 Supplied With White Bezel



GENERAL INFORMATION	
Product Code	NPC/WH/MW/830-40-65
Product Range	Amenity
Product Category	Amenity
IP Rating	65
IK Rating	N/A
Warranty	5 Years Unlimited
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=Ø315, H=79
Dimensions Square/Rectangular (L x W x H) (mm)	L=0, W=0, H=0
Cut-out Size (mm)	0
Product Weight (Kg)	0.7
CONSTRUCTION	
Body Material	PC
Body Colour	White
Optical Material	N/A
Optical Finish	N/A
Termination	4x2x2.5mm sq. Push In Terminal
Driver - Integral or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	F
Luminaire Lumens (lm)	(9W) 990 - 1057 - 1028 (14W) 1410 - 1518 - 1488 (18W) 1661 - 1858 - 1689
Power Consumption (W)	9.3 - 8.9 - 9.2 / 14.11 - 13.4 - 14 / 17.8 - 16.7 - 17.5
LED Lumens (lm/W)	N/A
Efficacy (l.lm/c.W)	106 - 119 - 112 / 100 - 113 - 106 / 93 - 111 - 97
Operating Temp. (Min/Max)	-20°C to 25°C to
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	3000 - 4000 - 6500
Colour Rendering Index (CRI)	>80
Lumen Depreciation	L70 50000
SDCM	<5
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50/60Hz
In Rush	<25A
Drivers per MCB*	B10=16 B16=28
Class	Class 1
Power Factor	>0.95
Cable Entry	Back
ELECTRICAL OUTPUT	
Forward Current (mA)	100 - 150 - 180
Forward Voltage (Vf)	86.1
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Emergency Lumens	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	Yes
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5056673209481

* GUIDE ONLY

