

## DATASHEET

### PHOENIX

Phoenix LED 40W 5Ft 850

IP20 Traditional LED Batten Fitting  
 Full Range Of Attachments  
 Direct Replacement For Traditional Battens



GENERAL INFORMATION	
Product Code	NPH40/LED/850
Product Range	Surface Mount
Product Category	Surface Mount
IP Rating	20
IK Rating	N/A
Warranty	7 Years Unlimited
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=N/A
Dimensions Square/Rectangular (L x W x H) (mm)	L=1527, W=61, H=64
Cut-out Size (mm)	N/A
Product Weight (Kg)	2.05
CONSTRUCTION	
Body Material	Steel Body
Body Colour	White
Optical Material	N/A
Optical Finish	N/A
Termination	3x2x2.5mm sq. Push In Terminal
Driver - Integal or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	C
Luminaire Lumens (lm)	5633
Power Consumption (W)	40
LED Lumens (lm/W)	165
Efficacy (l.lm/c.W)	151
Operating Temp. (Min/Max)	-20°C to 25°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	5000
Colour Rendering Index (CRI)	>80
Lumen Depreciation	L80 100000
SDCM	<3
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50/60Hz
In Rush	<25A
Drivers per MCB*	B10=16 B16=28
Class	Class 1
Power Factor	>0.95
Cable Entry	Ends / Back
ELECTRICAL OUTPUT	
Forward Current (mA)	1060
Forward Voltage (Vf)	31
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Emergency Lumens	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5055825966944

\* GUIDE ONLY

