

DATASHEET

SENECA LIFE

Seneca LiFe LED Non-Maint. Surf Mount DALI Oval Lens

IP65 Dedicated LED Surface Emergency Fittings
 Oval Lens Gives Escape Route Lighting
 Lithium Iron Phosphate (LiFePO4) Battery



GENERAL INFORMATION	
Product Code	NSC/SURF-O/DA/NM3
Product Range	Emergency
Product Category	Emergency
IP Rating	65
IK Rating	N/A
Warranty	7 Years Unlimited
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=47
Dimensions Square/Rectangular (L x W x H) (mm)	L=160, W=160, H=52
Cut-out Size (mm)	N/A
Product Weight (Kg)	0.3
CONSTRUCTION	
Body Material	PC
Body Colour	White
Optical Material	N/A
Optical Finish	N/A
Termination	3x2x2.5mm sq. Push In Terminal
Driver - Integal or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	200
Power Consumption (W)	1.3
LED Lumens (lm/W)	N/A
Efficacy (l.lm/c.W)	N/A
Operating Temp. (Min/Max)	0°C to 35°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	5700
Colour Rendering Index (CRI)	N/A
Lumen Depreciation	N/A
SDCM	N/A
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50/60Hz
In Rush	N/A
Drivers per MCB*	N/A
Class	Class 2
Power Factor	>0.58
Cable Entry	Back
ELECTRICAL OUTPUT	
Forward Current (mA)	-
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	Non-Maintained
Battery Duration	3 Hours
Battery Type	LiFePO4
Battery Specification	3.2V 3000mAh
Emergency Lumens	N/A
DIMMING	
DALI	Yes
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5056673202031

* GUIDE ONLY

