

DATASHEET

SPARTAN

Spartan LED IP65 White Base MW M3 Lithium 830-40-50

IP65 Polycarbonate LED Bulkhead
 Commercial Indoor And Outdoor Areas
 Easy To Install



GENERAL INFORMATION	
Product Code	NSP/WH/CFMW/M3/830-40-50
Product Range	Amenity
Product Category	Amenity
IP Rating	65
IK Rating	IK10
Warranty	5 Years Core
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=Ø278, H=75
Dimensions Square/Rectangular (L x W x H) (mm)	L=0, W=0, H=0
Cut-out Size (mm)	0
Product Weight (Kg)	1.1
CONSTRUCTION	
Body Material	PC
Body Colour	White
Optical Material	N/A
Optical Finish	N/A
Termination	5x2x1.5mm sq. Push In Terminal
Driver - Integal or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	E
Luminaire Lumens (lm)	1220
Power Consumption (W)	11.2
LED Lumens (lm/W)	165
Efficacy (l.lm/c.W)	109
Operating Temp. (Min/Max)	0°C to 25°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	3000 / 4000 / 5000
Colour Rendering Index (CRI)	>80
Lumen Depreciation	L80 100000
SDCM	<3
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50/60Hz
In Rush	<25A
Drivers per MCB*	B10=16 B16=28
Class	Class 1
Power Factor	>0.95
Cable Entry	Side / Back
ELECTRICAL OUTPUT	
Forward Current (mA)	-
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	Maintained
Battery Duration	3 Hours
Battery Type	LiFePO4
Battery Specification	6.4V 1Ah
Emergency Lumens	8.93
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	YES
SENSORS	
Microwave	Yes
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5055943085251

* GUIDE ONLY

Image not found or type unknown

