

DATASHEET

STERLING PRO

Sterling Pro 17-28W UGR<19 LED Panel 600x600 TPA 840

IP44 TP(a) Recessed LED Panel
 PMMA Light Guide Plate With MP Polycarbonate Diffuser
 ENEC Flicker Free Driver



GENERAL INFORMATION	
Product Code	NST17-28/O/66/840
Product Range	LED Panels
Product Category	LED Panels
IP Rating	44
IK Rating	N/A
Warranty	7 Years
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=34
Dimensions Square/Rectangular (L x W x H) (mm)	L=595, W=595, H=N/A
Cut-out Size (mm)	N/A
Product Weight (Kg)	2.45
CONSTRUCTION	
Body Material	PC
Body Colour	White
Optical Material	N/A
Optical Finish	N/A
Termination	3x2x2.5mm sq. Push In Terminal
Driver - Integal or Remote	Remote
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A


LUMINAIRE PERFORMANCE	
Energy Rating	C
Luminaire Lumens (lm)	3129 / 3431 / 3750 / 4063 / 4370 / 4676 / 4949
Power Consumption (W)	17-28
LED Lumens (lm/W)	N/A
Efficacy (l.lm/c.W)	181
Operating Temp. (Min/Max)	0°C to 40°C .
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	4000
Colour Rendering Index (CRI)	>80
Lumen Depreciation	L80 100000
SDCM	<3
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50/60Hz
In Rush	N/A
Drivers per MCB*	N/A
Class	Class 2
Power Factor	>0.95
Cable Entry	Prewired
ELECTRICAL OUTPUT	
Forward Current (mA)	N/A
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Emergency Lumens	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	N/A

* GUIDE ONLY

34



/66 = 595
/123 = 295
/126 = 595



/66 = 595
/123 = 1195
/126 = 1195

