

DATASHEET

STERLING PRO

Sterling Pro 17-40W UGR<19 LED Panel 1200x600 TPA DD
 830

IP44 TP(a) Recessed LED Panel
 PMMA Light Guide Plate With MP Polycarbonate Diffuser
 ENEC Flicker Free Driver




GENERAL INFORMATION	
Product Code	NST17-40/UGR/126/DD/830
Product Range	LED Panels
Product Category	LED Panels
IP Rating	44
IK Rating	N/A
Warranty	7 Years
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=34
Dimensions Square/Rectangular (L x W x H) (mm)	L=1195, W=595, H=N/A
Cut-out Size (mm)	N/A
Product Weight (Kg)	2.45
CONSTRUCTION	
Body Material	PC
Body Colour	White
Optical Material	N/A
Optical Finish	N/A
Termination	3x2x2.5mm sq. Push In Terminal
Driver - Integal or Remote	Remote
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight inclc. Carton (Kg)	N/A


LUMINAIRE PERFORMANCE	
Energy Rating	C
Luminaire Lumens (lm)	2978 / 3288 / 3597 / 3903 / 4200 / 4520 / 4790 / 5087 / 5372 / 5672 / 5957 / 6256 / 6587
Power Consumption (W)	17-40
LED Lumens (lm/W)	N/A
Efficacy (l.lm/c.W)	172
Operating Temp. (Min/Max)	0°C to 40°C .
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	3000
Colour Rendering Index (CRI)	>80
Lumen Depreciation	L80 100000
SDCM	<3
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50/60Hz
In Rush	<25A
Drivers per MCB*	B10=16 B16=28
Class	Class 2
Power Factor	>0.95
Cable Entry	Prewired
ELECTRICAL OUTPUT	
Forward Current (mA)	640
Forward Voltage (Vf)	33
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Emergency Lumens	N/A
DIMMING	
DALI	Yes
OTHER	N/A
Switch Dim	Yes
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5056673232168

* GUIDE ONLY

34



/66 = 595
/123 = 295
/126 = 595



/66 = 595
/123 = 1195
/126 = 1195

