NVC UK - NVC Lighting Limited
NVC Park 201, Hollymoor Way, Rubery,
Birmingham, B31 5HE
T +44 (0)121 457 6340
E sales@nvcuk.com

NVC NORDICS - NVC Lighting AB
Albybergsringen 3b 137 69 Österhaninge
T +46(0)8 735 55 40
Sweden info@nvc-lighting.se

DATASHEET

TEMPE PRO

Tempe Pro 40-70W LED 1500mm Trunking Batten 840

Energy Efficiency Classification Class C
Hinged Gear Tray For Easy Access
5-Pole Through Wired With Tool-Less Access

GENERAL INFORMATION	
Product Code	NTM/5/40-70/DD/HR/840
Product Range	Surface Mount
Product Category	Surface Mount
IP Rating	23
IK Rating	N/A
Warranty	7 years
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=N/A
Dimensions Square/Rectangular (L x W x H) (mm)	L=1550, W=92, H=50
Cut-out Size (mm)	N/A
Product Weight (Kg)	5.1
CONSTRUCTION	
Body Material	Steel
Body Colour	White RAL9003
Optical Material	N/A
Optical Finish	N/A
Termination	5x2x2.5mm sq. Push In Terminal
Driver - Intergal or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight inlc. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	7237 / 8819 / 10441 / 12046
Power Consumption (W)	41 / 50 / 60 / 70
LED Lumens (lm/W)	N/A
Efficacy (l.lm/c.W)	176 / 176 / 174 / 173
Operating Temp. (Min/Max)	-20°C to 45°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	4000
Colour Rendering Index (CRI)	>80
Lumen Depreciation	L80 100000
SDCM	<3
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50
In Rush	<25A
Drivers per MCB*	B10=4 B16=8 C10=8 C16=16
Class	Class 1
Power Factor	>0.95
Cable Entry	Ends
ELECTRICAL OUTPUT	
Forward Current (mA)	-
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Emergency Lumens	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5056673237682

* GUIDE ONLY





Beam angle **56.8°**

ISO 9001 FS 690066 ISO 14001 EMS 716023 ISO 45001 OHS 716024
ECA REGISTERED MEMBER
EDA
FORS FLEET OPERATOR RECOGNITION SCHEME ID:012687
RELUX official member