

DATASHEET

TEMPE PRO

Tempe Pro 80-120W LED 1500mm Trunking Batten 840

Energy Efficiency Classification Class C
 Hinged Gear Tray For Easy Access
 5-Pole Through Wired With Tool-Less Access



GENERAL INFORMATION	
Product Code	NTM/5/80-120/DD/HR/840
Product Range	Surface Mount
Product Category	Surface Mount
IP Rating	23
IK Rating	N/A
Warranty	7 years
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=N/A
Dimensions Square/Rectangular (L x W x H) (mm)	L=1550, W=92, H=50
Cut-out Size (mm)	N/A
Product Weight (Kg)	N/A
CONSTRUCTION	
Body Material	Steel
Body Colour	White RAL9003
Optical Material	N/A
Optical Finish	N/A
Termination	5x2x2.5mm sq. Push In Terminal
Driver - Integal or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	8457 / 9471 / 11353 / 12383 / 14058 / 14932 / 16164 / 17143 / 18169 / 19698
Power Consumption (W)	46.1 / 52.8 / 63.6 / 71 / 80 / 85.6 / 91.5 / 99.9 / 105.9 / 119.4
LED Lumens (lm/W)	N/A
Efficacy (l.lm/c.W)	183 / 179 / 179 / 174 / 176 / 176 / 177 / 172 / 172 / 165
Operating Temp. (Min/Max)	-20°C to 45°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	4000
Colour Rendering Index (CRI)	>80
Lumen Depreciation	L80 100000
SDCM	<3
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50
In Rush	<25A
Drivers per MCB*	B10=4 B16=8 C10=8 C16=16
Class	Class 1
Power Factor	>0.95
Cable Entry	Ends
ELECTRICAL OUTPUT	
Forward Current (mA)	-
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Emergency Lumens	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	N/A

* GUIDE ONLY

