

NVC UK - NVC Lighting Limited  
NVC Park 201, Hollymoor Way, Rubery,  
Birmingham, B31 5HE  
T +44 (0)121 457 6340  
E sales@nvcuk.com

NVC NORDICS - NVC Lighting AB  
Albybergsringen 3b 137 69 Österhaninge  
T +46(0)8 735 55 40  
Sweden info@nvc-lighting.se



## DATASHEET

### TEXAS PRO

Texas Pro 18-23-27-32W LED Batten Low Output 5Ft DD Dim  
M3L 830-840-860

IP20 Surface LED Fitting  
Steel And Polycarbonate Construction  
ENEC Approved Flicker Free Driver



| GENERAL INFORMATION                            |                                |
|------------------------------------------------|--------------------------------|
| Product Code                                   | NTE5/18-32/DD/M3L/830-40-60    |
| Product Range                                  | Surface Mount                  |
| Product Category                               | Surface Mount                  |
| IP Rating                                      | 20                             |
| IK Rating                                      | N/A                            |
| Warranty                                       | 7 Years                        |
| DIMENSION/WEIGHT                               |                                |
| Dimensions Circular (DIA x H) (mm)             | DIA=N/A, H=N/A                 |
| Dimensions Square/Rectangular (L x W x H) (mm) | L=1464, W=62, H=72             |
| Cut-out Size (mm)                              | N/A                            |
| Product Weight (Kg)                            | 1.46                           |
| CONSTRUCTION                                   |                                |
| Body Material                                  | PC/Steel                       |
| Body Colour                                    | White                          |
| Optical Material                               | N/A                            |
| Optical Finish                                 | N/A                            |
| Termination                                    | 3x2x2.5mm sq. Push In Terminal |
| Driver - Intergal or Remote                    | Integral                       |
| PACKAGING                                      |                                |
| Carton Dimensions (mm)                         | N/A                            |
| Quantity per Outer Carton                      | N/A                            |
| Total Weight inclc. Carton (Kg)                | N/A                            |

| LUMINAIRE PERFORMANCE        |                             |
|------------------------------|-----------------------------|
| Energy Rating                | D                           |
| Luminaire Lumens (lm)        | 2924 / 3747 / 4439 / 5187   |
| Power Consumption (W)        | 17.6 / 22.4 / 26.7 / 31.4   |
| LED Lumens (lm/W)            | N/A                         |
| Efficacy (l.lm/c.W)          | 161 / 167 / 166 / 165       |
| Operating Temp. (Min/Max)    | 0°C to 40°C                 |
| LIGHT SOURCE                 |                             |
| Type                         | LED                         |
| Correlated Colour Temp.      | 3000 / 4000 / 6000          |
| Colour Rendering Index (CRI) | >80                         |
| Lumen Depreciation           | L80 100000                  |
| SDCM                         | <3                          |
| ELECTRICAL INPUT             |                             |
| VOLTAGE (V)                  | 220-240V AC                 |
| Operating Frequency          | 50/60Hz                     |
| In Rush                      | <25A                        |
| Drivers per MCB*             | B10=10 B16=15 C10=15 C16=20 |
| Class                        | Class 1                     |
| Power Factor                 | >0.95                       |
| Cable Entry                  | Side / Base                 |
| ELECTRICAL OUTPUT            |                             |
| Forward Current (mA)         | N/A                         |
| Forward Voltage (Vf)         | N/A                         |
| EMERGENCY DATA               |                             |
| Mode of Operation            | N/A                         |
| Battery Duration             | 3 Hours                     |
| Battery Type                 | LiFePO4                     |
| Battery Specification        | 2-cell 6.4V 1.6Ah           |
| Emergency Lumens             | N/A                         |
| DIMMING                      |                             |
| DALI                         | Yes                         |
| OTHER                        | N/A                         |
| Switch Dim                   | Yes                         |
| Corridor Function            | N/A                         |
| SENSORS                      |                             |
| Microwave                    | N/A                         |
| PIR                          | N/A                         |
| STANDARDS/APPROVALS          |                             |
| CE Marked                    | Yes                         |
| Certificate of Conformity    | Yes                         |
| Accreditations               | N/A                         |
| BARCODE                      |                             |
| EAN NUMBER                   | 5056673235398               |

\* GUIDE ONLY

