

NVC UK - NVC Lighting Limited  
NVC Park 201, Hollymoor Way, Rubery,  
Birmingham, B31 5HE  
T +44 (0)121 457 6340  
E sales@nvcuk.com

NVC NORDICS - NVC Lighting AB  
Albybergsringen 3b 137 69 Österhaninge  
T +46(0)8 735 55 40  
Sweden info@nvc-lighting.se



## DATASHEET

### TEXAS PRO

Texas Pro 29-37-45-52W LED Batten High Output 5Ft DD Dim  
M3L 830-840-860

IP20 Surface LED Fitting  
Steel And Polycarbonate Construction  
ENEC Approved Flicker Free Driver



#### GENERAL INFORMATION

|                  |                             |
|------------------|-----------------------------|
| Product Code     | NTE5/29-52/DD/M3L/830-40-60 |
| Product Range    | Surface Mount               |
| Product Category | Surface Mount               |
| IP Rating        | 20                          |
| IK Rating        | N/A                         |
| Warranty         | 7 Years                     |

#### DIMENSION/WEIGHT

|                                                |                    |
|------------------------------------------------|--------------------|
| Dimensions Circular (DIA x H) (mm)             | DIA=N/A, H=N/A     |
| Dimensions Square/Rectangular (L x W x H) (mm) | L=1464, W=62, H=72 |
| Cut-out Size (mm)                              | N/A                |
| Product Weight (Kg)                            | 1.46               |

#### CONSTRUCTION

|                             |                                |
|-----------------------------|--------------------------------|
| Body Material               | PC/Steel                       |
| Body Colour                 | White                          |
| Optical Material            | N/A                            |
| Optical Finish              | N/A                            |
| Termination                 | 3x2x2.5mm sq. Push In Terminal |
| Driver - Intergal or Remote | Integral                       |

#### PACKAGING

|                                |     |
|--------------------------------|-----|
| Carton Dimensions (mm)         | N/A |
| Quantity per Outer Carton      | N/A |
| Total Weight incl. Carton (Kg) | N/A |

#### LUMINAIRE PERFORMANCE

|                           |                           |
|---------------------------|---------------------------|
| Energy Rating             | D                         |
| Luminaire Lumens (lm)     | 4794 / 5923 / 7058 / 8132 |
| Power Consumption (W)     | 28.6 / 35.5 / 43.1 / 50.5 |
| LED Lumens (lm/W)         | N/A                       |
| Efficacy (l.lm/c.W)       | 168 / 167 / 164 / 162     |
| Operating Temp. (Min/Max) | 0°C to 40°C               |

#### LIGHT SOURCE

|                              |                    |
|------------------------------|--------------------|
| Type                         | LED                |
| Correlated Colour Temp.      | 3000 / 4000 / 6000 |
| Colour Rendering Index (CRI) | >80                |
| Lumen Depreciation           | L80 100000         |
| SDCM                         | <3                 |

#### ELECTRICAL INPUT

|                     |                             |
|---------------------|-----------------------------|
| VOLTAGE (V)         | 220-240V AC                 |
| Operating Frequency | 50/60Hz                     |
| In Rush             | <25A                        |
| Drivers per MCB*    | B10=10 B16=15 C10=15 C16=20 |
| Class               | Class 1                     |
| Power Factor        | >0.95                       |
| Cable Entry         | Side / Base                 |

#### ELECTRICAL OUTPUT

|                      |     |
|----------------------|-----|
| Forward Current (mA) | N/A |
| Forward Voltage (Vf) | N/A |

#### EMERGENCY DATA

|                       |                   |
|-----------------------|-------------------|
| Mode of Operation     | N/A               |
| Battery Duration      | 3 Hours           |
| Battery Type          | LiFePO4           |
| Battery Specification | 2-cell 6.4V 1.6Ah |
| Emergency Lumens      | N/A               |

#### DIMMING

|                   |     |
|-------------------|-----|
| DALI              | Yes |
| OTHER             | N/A |
| Switch Dim        | Yes |
| Corridor Function | N/A |

#### SENSORS

|           |     |
|-----------|-----|
| Microwave | N/A |
| PIR       | N/A |

#### STANDARDS/APPROVALS

|                           |     |
|---------------------------|-----|
| CE Marked                 | Yes |
| Certificate of Conformity | Yes |
| Accreditations            | N/A |

#### BARCODE

|            |               |
|------------|---------------|
| EAN NUMBER | 5056673235404 |
|------------|---------------|

\* GUIDE ONLY

