NVC UK - NVC Lighting Limited
NVC Park 201, Hollymoor Way, Rubery,
Birmingham, B31 5HE
T +44 (0)121 457 6340
E sales@nvcuk.com

NVC NORDICS - NVC Lighting AB
Albybergsringen 3b 137 69 Österhaninge
T +46(0)8 735 55 40
Sweden info@nvc-lighting.se
Finland info@nvclighting.fi
Denmark info@nvclighting.dk

DATASHEET

TULSA V4

Tulsa V4 Opal Edge Lit LED Panel 600X600 830 No Driver

Energy Efficiency Classification Class D
Edge-Lit LED Technology
Driver Supplied As Separate Item

GENERAL INFORMATION	
Product Code	BB/NTU/O/66/830/ND
Product Range	LED Panels
Product Category	LED Panels
IP Rating	44
IK Rating	N/A
Warranty	7 Years
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=N/A
Dimensions Square/Rectangular (L x W x H) (mm)	L=595, W=595, H=9
Cut-out Size (mm)	N/A
Product Weight (Kg)	2.7
CONSTRUCTION	
Body Material	Extruded Aluminium
Body Colour	White RAL9016
Optical Material	N/A
Optical Finish	N/A
Termination	On driver (Supplied separately)
Driver - Intergal or Remote	Remote (Supplied separately)
PACKAGING	
Carton Dimensions (mm)	620x620x30
Quantity per Outer Carton	N/A
Total Weight inlc. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	D
Luminaire Lumens (lm)	3310/4192
Power Consumption (W)	24.1 (24W) / 28.2 (28W)
LED Lumens (lm/W)	N/A
Efficacy (l.lm/c.W)	149
Operating Temp. (Min/Max)	-20°C to 25°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	3000
Colour Rendering Index (CRI)	>80
Lumen Depreciation	L90 100000
SDCM	<3
ELECTRICAL INPUT	
VOLTAGE (V)	See driver
Operating Frequency	See driver
In Rush	See driver
Drivers per MCB*	See driver
Class	Class 2
Power Factor	See driver
Cable Entry	On Driver
ELECTRICAL OUTPUT	
Forward Current (mA)	-
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Emergency Lumens	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5055943087361
S NUMBER	4266515

* GUIDE ONLY