

DATASHEET

ACCESSORIES

LiFe High Bay IP65 STNM3 Emergency Pack

Plug And Play Option For A Range Of Fittings
 High Output Easy Installation
 Lithium Iron Phosphate Battery LiFePO4



GENERAL INFORMATION	
Product Code	N/HB/STNM3L/PACK
Product Range	LED Panels
Product Category	LED Panels
IP Rating	N/A
IK Rating	N/A
Warranty	7 Years
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=N/A
Dimensions Square/Rectangular (L x W x H) (mm)	L=330, W=61, H=30
Cut-out Size (mm)	N/A
Product Weight (Kg)	0.41
CONSTRUCTION	
Body Material	PC
Body Colour	White
Optical Material	N/A
Optical Finish	N/A
Termination	4x2x2.5mm sq. Push In Terminal
Driver - Intergal or Remote	Remote
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight inc. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	1319
Power Consumption (W)	8
LED Lumens (lm/W)	N/A
Efficacy (l.lm/c.W)	165
Operating Temp. (Min/Max)	0°C to 40°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	N/A
Colour Rendering Index (CRI)	N/A
Lumen Depreciation	N/A
SDCM	N/A
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50/60Hz
In Rush	N/A
Drivers per MCB*	N/A
Class	Class 2
Power Factor	N/A
Cable Entry	Prewired
ELECTRICAL OUTPUT	
Forward Current (mA)	35 to 100
Forward Voltage (Vf)	20 to 55
EMERGENCY DATA	
Mode of Operation	Non-Maintained
Battery Duration	3 hours
Battery Type	LiFePO4
Battery Specification	6.4V 1.5Ah
Ballast Lumen Factor (BLF)	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5056673203762
E NUMBER	7347969
S NUMBER	4339171

* GUIDE ONLY

