

DATASHEET

MONTANA

Montana 9-12-15W LED 150mm Cutout 2m Plug+Lead 830-840

IP54 Low Glare LED Recessed Downlight
 White Die Cast Aluminium Bezel
 Aluminium Semi Specular Reflector



GENERAL INFORMATION	
Product Code	NMT9-12-15/PL/830-840
Product Range	Downlights
Product Category	Downlights
IP Rating	54
IK Rating	N/A
Warranty	N/A
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=Ø176, H=86
Dimensions Square/Rectangular (L x W x H) (mm)	L=0, W=0, H=0
Cut-out Size (mm)	Ø150
Product Weight (Kg)	0
CONSTRUCTION	
Body Material	PC / Die Cast Aluminium
Body Colour	White
Optical Material	N/A
Optical Finish	N/A
Termination	N/A
Driver - Intergal or Remote	Remote
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	D
Luminaire Lumens (lm)	1278 / 1662 / 2096
Power Consumption (W)	9 / 12 / 15
LED Lumens (lm/W)	N/A
Efficacy (Llm/c.W)	144 / 136 / 140
Operating Temp. (Min/Max)	-20°C to 40°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	3000-4000
Colour Rendering Index (CRI)	>80
Lumen Depreciation	L80 100000
SDCM	<3
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50/60Hz
In Rush	N/A
Drivers per MCB*	B10=45 B16=54 C10=72 C16=87
Class	Class 2
Power Factor	N/A
Cable Entry	N/A
ELECTRICAL OUTPUT	
Forward Current (mA)	N/A
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Ballast Lumen Factor (BLF)	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5056673229823
E NUMBER	7029050

* GUIDE ONLY

6" Fitting (9-12-15W)

