

DATASHEET

TEMPE PRO

Tempe Pro 40-70W LED 1500mm Trunking Batten DD 840

Energy Efficiency Classification Class C
 Hinged Gear Tray For Easy Access
 7-Pole Through Wired With Tool-Less Access



GENERAL INFORMATION	
Product Code	NTM/5/40-70/DD/840
Product Range	Surface Mount
Product Category	Surface Mount
IP Rating	23
IK Rating	N/A
Warranty	7 Years
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=N/A
Dimensions Square/Rectangular (L x W x H) (mm)	L=1550, W=92, H=50
Cut-out Size (mm)	N/A
Product Weight (Kg)	N/A
CONSTRUCTION	
Body Material	Steel
Body Colour	White RAL9003
Optical Material	N/A
Optical Finish	N/A
Termination	7x2x2.5mm sq. Push In Terminal
Driver - Intergal or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	7606 / 9081 / 10588 / 12289
Power Consumption (W)	41.8 / 51 / 60.2 / 70.5
LED Lumens (lm/W)	N/A
Efficacy (Llm/c.W)	178 / 178 / 176 / 174
Operating Temp. (Min/Max)	-20°C to 25°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	4000
Colour Rendering Index (CRI)	>80
Lumen Depreciation	L80 100000
SDCM	<3
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50
In Rush	<25A
Drivers per MCB*	B10=4 B16=8 C10=8 C16=16
Class	Class 1
Power Factor	>0.95
Cable Entry	Ends
ELECTRICAL OUTPUT	
Forward Current (mA)	-
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Ballast Lumen Factor (BLF)	N/A
DIMMING	
DALI	Yes
OTHER	N/A
Switch Dim	Yes
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5056673204509
E NUMBER	7218736
S NUMBER	4314369

* GUIDE ONLY

