

DATASHEET

TEMPE

Tempe Horizontal Wire Fixing Kit

Wire Suspension Kit
 For Suspended Installations
 Easy To Install



| GENERAL INFORMATION | |
|------------------------------------------------|-----------------|
| Product Code | NTM/H-WIRE/KIT |
| Product Range | Surface Mount |
| Product Category | Surface Mount |
| IP Rating | N/A |
| IK Rating | N/A |
| Warranty | N/A |
| DIMENSION/WEIGHT | |
| Dimensions Circular (DIA x H) (mm) | DIA=N/A, H=N/A |
| Dimensions Square/Rectangular (L x W x H) (mm) | L=0, W=0, H=N/A |
| Cut-out Size (mm) | N/A |
| Product Weight (Kg) | 0.1 |
| CONSTRUCTION | |
| Body Material | Aluminium |
| Body Colour | N/A |
| Optical Material | N/A |
| Optical Finish | N/A |
| Termination | N/A |
| Driver - Intergal or Remote | N/A |
| PACKAGING | |
| Carton Dimensions (mm) | N/A |
| Quantity per Outer Carton | N/A |
| Total Weight incl. Carton (Kg) | N/A |

| LUMINAIRE PERFORMANCE | |
|------------------------------|---------------|
| Energy Rating | N/A |
| Luminaire Lumens (lm) | N/A |
| Power Consumption (W) | N/A |
| LED Lumens (lm/W) | N/A |
| Efficacy (l.lm/c.W) | N/A |
| Operating Temp. (Min/Max) | N/A 25°C |
| LIGHT SOURCE | |
| Type | N/A |
| Correlated Colour Temp. | N/A |
| Colour Rendering Index (CRI) | N/A |
| Lumen Depreciation | N/A |
| SDCM | N/A |
| ELECTRICAL INPUT | |
| VOLTAGE (V) | N/A |
| Operating Frequency | N/A |
| In Rush | N/A |
| Drivers per MCB* | N/A |
| Class | N/A |
| Power Factor | N/A |
| Cable Entry | N/A |
| ELECTRICAL OUTPUT | |
| Forward Current (mA) | N/A |
| Forward Voltage (Vf) | N/A |
| EMERGENCY DATA | |
| Mode of Operation | N/A |
| Battery Duration | N/A |
| Battery Type | N/A |
| Battery Specification | N/A |
| Ballast Lumen Factor (BLF) | N/A |
| DIMMING | |
| DALI | N/A |
| OTHER | N/A |
| Switch Dim | N/A |
| Corridor Function | N/A |
| SENSORS | |
| Microwave | N/A |
| PIR | N/A |
| STANDARDS/APPROVALS | |
| CE Marked | Yes |
| Certificate of Conformity | Yes |
| Accreditations | N/A |
| BARCODE | |
| EAN NUMBER | 5055943063587 |
| E NUMBER | 7904069 |

* GUIDE ONLY

